

Capture Lite (Calibration Analyser) cont.

		CL 1	CL10H	CL10S	CL150	CL350	CL1500
Dimension							
Total width (inch)	"						
Total width [mm]	mm	120	120	120	120	120	
Total height (inch)	"						
Total height [mm]	mm	70	70	70	70	70	
Total depth [mm]	mm						
Total length (inch)							
Total length [mm]	mm	135	135	135	135	135	
Net weight [g]	g						
Net weight [kg]	kg	1.32	1.42	1.42	1.52	1.65	
Classification							
Adaptor		None	FSHA	None	1/4"	3/8"	3/4"
Drive connector hexagon male (metric)		6.3	6.3				
Drive connector hexagon male [inch]		1/4"	1/4"				
Drive connector square female (metric)	mm			6.3	10	12.5	
Drive connector square female [inch]				1/4"	3/8"	1/2"	1"
Resolution		0.0001	.001	.001	.01	.01	.1
Operating direction		right	right	right	right	right	right
Torque (max.) [lbf-ft]	lbf-ft	0.74	7.4	7.4	110	260	1100
Torque (min.) [lbf-in]	lbf-in	8.8	88	88	1325	3100	13300
Torque (max.) [N-m]	N-m	1	10	10	150	350	1500
Torque (min.) [lbf-ft]	lbf-ft	0.015	1.9	1.9	3.7	7.4	55
Torque (max.) [lbf-in]	lbf-in	0.18	2.2	2.2	44	88	665
Torque (min.) [N-m]	N-m	0.02	0.25	0.25	5	10	75
Torque range (min./max.) [lbf-ft]		0.015lbf-ft - 0.74lbf-ft	1.9lbf-ft - 7.4lbf-ft	1.9lbf-ft - 7.4lbf-ft	3.7lbf-ft - 110lbf-ft	7.4lbf-ft - 260lbf-ft	55lbf-ft - 1100lbf-ft
Torque range (min./max.) [N-m]		0,02 N-m - 1 N-m	0,25 N-m - 10 N-m	0,25 N-m - 10 N-m	5 N-m - 150 N-m	10 N-m - 350 N-m	75 N-m - 1500 N-m
Housing shape							
Graphic display		OLED	OLED	OLED	OLED	OLED	OLED
Material		aluminium body	aluminium body	aluminium body	aluminium body	aluminium body	aluminium body
Measurement accuracy		1%	1%	1%	1%	1%	1%
Standard							
REACH registration available							
Interface		USB	USB	USB	USB	USB	USB